ISUZU MOTORS AMERICA, LLC	MODEL	4LE2TAGV09
PowerTrain Division	ISZJ SPEC NO.	IS-21-028-0
	DWG NO./DATE	E3-1038-214-0, 6/2/2021

					DWG NO./D	OATE E3-1038-214-0, 6/2/202 [,]	1
BASIC ENGINE DESCRIPTION		2.2L, 4 CYL, 4 STROKE, WTR COOLED, OHV, I/L, DIRECT INJECTED, TURBOCHARGED DIESEL B=85mm, S=96mm, CR=17.6:1, GLOW PLUG ASSISTED START, ELECTRONICALLY CONTROLLED, COMMON RAIL, COOLED EGR					
CONFIGURATION GENSI US EP		INDUST GENSE	TRIAL TURBO F/F T 12V	ENGINE PERFORMANCE		40.2 BHP @ 1800 RPM (STANDBY) * 33.5 BHP @ 1800 RPM (CONTINUOUS) *	
		US EPA	(Final Tier 4) Without ED		Fan IDLE SPEED: 1000 RPM MAX SPEED: 1800 RPM		
			EXH TCHGR EXH ADAPTOR			37.5 BHP @ 1800 RPM (STANDBY) ** 31.2 BHP @ 1800 RPM (CONTINUOUS) **	
SPECIFIC OEM INFORMATION		ISZA ST	ΓD	DATE OF ISSUE:	3/7/2024 ISZA	DATE RELEASED: PREVIOUS ISSUE DATE:	7/14/2021 ISZA 9/9/2022 ISZA
			SPECIFI	CATION I	NFORMATIC	ON	
PART N	AME		PART NUMBER	TYPE		PART DESCRIPTION	
CRANKCASE B	BREA	THER	N/A		CLOSED T	YPE	
FLYWHEEL HSG			8-98226-260-0		SAE #4 w/METRIC THREADS w/FLAT SD MT PADS 158mm DP, w/TACH PORT 3/4"-16 @ ≈ 2 O'CLOCK		
DIESEL OXIDATION CATALYST (DOC)		8-98205-771-1		MOUNTED ON FW HSG			
OIL PAN		8-98244-006-0	ASM	10.4L MAX, 6.1L MIN, RH SD CTR DRAIN		N	
DIPSTICK		8-97490-503-0	GAUGE	INSTALLED ON RH CYL BLK			
FLYWHEEL	YWHEEL		8-97252-438-2 N/A	ASM BRG HOLDER	SAE 10" OVER CTR CLUTCH w/PILOT BRG BORE w/DRIVE RING Z=108		BRG BORE
CRANKSHAFT PULLEY 8-98		8-98094-099-1		EFF DIA=132mm, SINGLE GROOVE, w/PTO PROVISION		РТО	
OIL FILTER		N/A 8-94456-741-2	ASM ELEM	SYSTEM; FULL FLOW w/REPLACEABLE SPIN-ON PAPER ELEM TYPE FILTER ATTACHES TO OIL COOLER @ ENG RR RH SD			
FUEL FILTER			SHIPPED LOOSE				
WATER PUMP		8-98210-172-2	ASM	CENTRIFUGAL VANE TYPE, WTR HRZ INL TWD RH SD OD=34mm HIGH FLOW		INL TWD RH	
WATER OUTLET PIPE		8-97258-479-2		LH SDWD,	LH SDWD, OD=32mm, HIGH FLOW		
WATER INLET PIPE		N/A		SDWD, LOC RH SD, OD=32mm, INTEGRAL PART OF WTR PUMP		RAL PART OF	
COOLING FAN		N/A					
FAN PULLEY		8-94459-815-4		1-GROOVE	E EFF DIA=118mm RATIO=1.	12:1	
FAN SPACER		SHIPPED LOOSE					
BOLT, FAN FIXING		N/A					
WASHER, FAN FIXING		N/A					
* Power after 70 hrs Engine Mo		lodel Spe	cification co	ntinued on the following pag	е.		
** Power at fact delivery	** Power at factory delivery						

This is a continuation of the engine specifications from the preceding page. 4LE2TAGV09	

proceding pa	90.			
PART NAME	PART NUMBER	TYPE	PART DESCRIPTION	
OIL COOLER	8-97102-320-0	ASM	MOUNTS BETWEEN OIL FILTER ADAPTER & CYL BLK @ ENG RR RH SD	
INLET MANIFOLD	8-98226-514-0		CTR INL LOC LH SD	
AIR INLET PIPE	8-98074-769-0		ANGLED DNWD	
EXHAUST MANIFOLD	8-98030-566-1		LH SD CTR OUTL TO TCHGR	
TURBOCHARGER	8-98223-617-0	ASM	IHI, OIL-COOLED TYPE, w/WASTE GATE, LOC LH SD, RRWD EXH, AIR INLET LH SD FACING FORWARD OD=39mm, AIR OUTLET UPWD	
EXHAUST ADAPTOR	8-98226-254-0		FACING RRWD	
MOUNTS	N/A			
STARTER	8-97112-865-2	ASM	DENSO 12V-2.0kW GEAR REDUCTION TYPE	
ALTERNATOR	8-97539-989-0	ASM	MITSUBISHI 12V-50A BUILT-IN REGULATOR NO TACH PROVISION	
GLOW PLUG	8-94133-759-9		QOS-II FOR 12V ELECTRIC	
FUEL FEED PUMP	SHIPPED LOOSE			
COOLANT TEMP SENSOR	8-98156-648-0			
OIL PRESSURE SENSOR	8-98027-456-0			
CRANKCASE PRESSURE SW	8-98319-376-0		P > 1 PSI = CLOSED	
ADAPTOR; SW	8-98337-718-0			
PTO DRIVE, GEAR SHAFT	N/A	ASM		
EMISSION LABEL	EPA ENGINE FAMILY NO. RSZXL02.2ZTB	EPA	FOR ENG HD COVER; FOR Y2024, EPA (Final Tier 4)	
	SPECIFICATION INF	ORMATIO	N FOR SHIP LOOSE ITEMS	
ENGINE CONTROL MODULE (ECM)	8-97506-211-0			
PCV HEATER	8-98192-467-0			
DOC EXH OUTLET GASKET	8-97373-108-0			
GASKET, EXH TCHGR ADAPTOR	8-97367-918-0			
SENSOR; INLET AIR TEMP	8-12146-830-0			
SENSOR; BAROMETRIC PRESSURE	8-97217-778-0			
PIPE ASM; FUEL FILTER	8-98126-332-0		QTY 4	
BOLT; EYE JOINT, OUT & IN	1-09675-193-0		QTY 4	
PACKING; FUEL PIPE	8-98251-345-0		QTY 8	
Engine Model Specification continued on the following page.				

PART NAME	PART NUMBER	TYPE	PART DESCRIPTION	
SPECIFICATION INFORMATION FOR SHIP LOOSE ITEMS (continued)				
FUEL FEED PUMP	8-98068-275-2	ASM	ELECTRIC, w/METAL SCREEN	
PRE FUEL FILTER w/WATER SEDIMENTER	8-98236-991-0 8-98240-279-0	ASM ELEM	PAPER ELEM TYPE wo/PRIMING PUMP, w/DRAIN, REMOTE MT	
MAIN FUEL FILTER w/WATER SEDIMENTER	8-98236-990-0 8-98240-280-0	ASM PAPER ELEM TYPE w/PRIMING PUMP & DRAIN, REMOTE MT		
FAN SPACER	8-97063-400-3		STEEL, L=4.5mm	
OWNER'S MANUAL	IDE-6450C		SPECIFIC TO FT4 4LE2T/X-SERIES	
EMISSION LABEL	EPA ENGINE FAMILY NO. RSZXL02.2ZTB	EPA	SUPPLEMENTAL LABEL FOR MACHINE; FOR Y2024, EPA (Final Tier 4)	

ADDITIONAL INFORMATION

OIL CHANGE INTERVAL: 500 HRS

OIL FILTER CHANGE INTERVAL: 250 HRS

MAXIMUM INCLINATION ANGLE: 15° ALL DIRECTIONS

FIRING ORDER: 1-3-4-2 COOLANT CAPACITY: 4.1L

ENGINE DRY WEIGHT: ≈217kg (478 lb) (NOT INCLUDING SHIP LOOSE ITEMS)

APPROXIMATE DIMENSIONS: HEIGHT 773mm, LENGTH 797mm, WIDTH 582mm

EPA-MANDATED FUEL TANK FILL LOCATION LABEL SAYING "ULTRA LOW SULFUR DIESEL FUEL ONLY" IS REQUIRED & MUST BE SUPPLIED & ATTACHED BY OEM.

NOTE: Part numbers are subject to change without notice.